

BRONZE SWING CHECK

125 - 150 - 200 - 300 LB

THREADED or SOLDER JOINT ENDS

SIZES: 1/8" to 4"

DESIGN DESCRIPTION


Threaded Cap
Bronze or Teflon Disc
Horizontal or Vertical Installation
Monel Trim available

PARTS AND MATERIAL LIST

DESCRIPTION	MATERIAL	SPECIFICATION
body	bronze	B62
cap	bronze	B62
disc	bronze	B61
hanger	bronze	B61
hanger pin	wrot silicon bronze	B371
disc nut	wrot silicon bronze	B371
side plug	wrot silicon bronze	B371

PRESSURE / TEMPERATURE RATINGS

See Globe Valves pg 9, 10



125 lb Standard 111501
125 lb Economy 110501

150 lb 112501
200 lb 113501
300 lb 114501



Solder Joint
191501

BRONZE LIFT CHECK

125 - 150 - 200 LB

THREADED ENDS

SIZES: 1/8" to 3"

DESIGN DESCRIPTION

Threaded Cap
Bronze or Teflon Disc
Horizontal Installation


Lift Checks are well adapted to pulsating operation and other services that would cause slamming and possible damage to the discs of swing check valves.

PARTS AND MATERIAL LIST:


DESCRIPTION	MATERIAL	SPECIFICATIONS
body	bronze	B62
cap	bronze	B62
disc	bronze	B62
nut	copper alloy	commercial

PRESSURE / TEMPERATURE RATINGS

See Globe Valves pg 9, 10



125 lb 111601
150 lb 112601
200 lb 113601



Lift Check Cutaway