



APPROVAL OF MANUFACTURER CERTIFICATE

Certificate No:
AMMM00001FT
Revision No:
2

This is to certify:

That

Neway Industrial (Suzhou) Co., Ltd.
No. 166, Kunlunshan Road, New District, SUZHOU, 215163 JIANGSU,
China

is an approved manufacturer of
Steel Castings

in accordance with
DNV rules for classification – Ships
DNV class programme – DNV-CP-0246 Steel castings

and the following particulars:

Application area	Castings for boilers, pressure vessels and piping systems, Stainless steel castings
Steel type	Carbon and carbon-manganese, Alloy, Austenitic stainless, Ferritic-austenitic (Duplex) stainless,
Casting method	Sand casting,
Max. weight	1 000 kg
Max. wall thickness	See page 2
Heat treatment condition	See page 2
Additional approval conditions	See page 2

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules.
Materials to be applied to DNV classed object shall fulfill the material requirements in the applicable DNV class rules.

Issued at **Hamburg** on **2023-04-19**

for **DNV**

This Certificate is valid until **2026-06-30**.

DNV local unit: **Shanghai**

Approval Engineer: **Andreas Koch**

.....
Thorsten Lohmann
Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: AM 311

Revision: 2022-12

www.dnv.com

Page 1 of 2

Particulars of the approval

Castings for boilers, pressure vessels and piping systems

Steel type	Grade ³⁾	Casting method ¹⁾	Max. weight [kg]	Max. wall thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	NV C450H, NV C490H	SC	1 000	120	N, NT, QT
Alloy	NV C0.5Mo, NV C1Cr0.5Mo, NV C2.25Cr1Mo	SC	1 000	120	N, NT, QT

Stainless steel castings

Steel type	Grade ³⁾	Casting method ¹⁾	Max. weight [kg]	Max. wall thickness [mm]	Heat treatment condition ²⁾
Austenitic	GX 2 CrNi 18 10 (304L) GX 5 CrNi 19 9 (304) GX 6 CrNiNb 19 10 (347) GX 2 CrNiMo 19 11 2 (316L) GX 5 CrNiMo 19 11 2 (316) GX 5 CrNiMo 19 11 3 (317)	SC	1 000	120	SHT
Ferritic-austenitic	GX 2 CrNiMoN 22 5 3	SC	1 000	120	SHT

Ferritic steel castings for low temperature service

Steel type	Grade ³⁾	Casting method ¹⁾	Max. weight [kg]	Max. wall thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	C450L, C490L	SC	1 000	120	N, NT, QT

Remarks:

- 1) SC: Sand Casting
- 2) SHT: Solution Heat Treated (Solution Annealing)
N: Normalized
QT: Quenched and tempered
NT: Normalized and tempered
- 3) Incl. equivalent grades in acc. to other standards

Special conditions: Including low temperature service for austenitic stainless steel